

## QUICK-LUB SEW LIQUID

**COMPOSITION** Polyethylene Emulsion

**USES** A high performance yarn lubricant and softener for exhaust application on package yarn, knits and pad application on woven cellulosic & blend substrates. Improves Sewability of knit goods & lubricity (coefficient of friction) of yarn.

**PROPERTIES**

- Gives fabrics a rich silky touch with surface softness.
- Reduced risk of needle damage to fabric and hole formation during garment stitching.
- Imparts natural comfort feel.
- Allows production of fabrics and garments with a high whiteness and minimal shade change on colored fabrics.

**TECHNICAL DATA**

- Off white to Creamish Liquid
- Non-ionic
- pH 7.5 – 9.5

### APPLICATION

<b>QUICK-LUB SEW</b>	1 - 3 % by exhaust application
pH	5.0 - 5.5 (adjusted with Acetic acid)
Time	20 - 30 min at 30 - 40°C (by exhaust)

Hydro extract and dry at 110 - 130°C without rinsing

<b>QUICK-LUB SEW</b>	10 - 40 g/l (by pad application)
pH	5.0 - 5.5 (adjusted with Acetic acid)

If combined with cellulose cross linking agents then details as per cross linking procedure should be followed.

**STORAGE** Stable for more than 6 months in closed containers at 20°C.

**ATTENTION** The above recommendations are based on comprehensive studies and experience made in practical finishing. They are, however, without liability regarding property rights of third parties and foreign laws. The user should test for himself whether the product and the application are suited for his very special purposes.

We are, above all, not liable for fields and methods of application which have not been put down by us in writing.

Advice for marking regulations and protective measures can be taken from the respective safety data sheet.